



48-Port IP DSLAM

The D-Link DAS-3248 is a 48-port IP-based DSL Access Multiplexer that provides ADSL access to CPE (consumer premise equipment) ADSL modems/routers at the subscriber side. This DSLAM connects to the network service provider's network through its Ethernet interface. Using the latest ADSL/ADSL2/ADSL2+ technology, this IP DSLAM provides carriers a very cost-effective solution to offer their subscribers with features such as bandwidth management, traffic prioritization and data flow security control.

Designed for Multi-Unit, Multi-Tenant Buildings

The D-Link DAS-3248 IP DSLAM delivers the next generation of high-performance business and residential DSL services. With the DAS-3248, carriers can offer digital video, high bandwidth Internet access.

48 ADSL Ports With Built-in Splitters

The DAS-3248 IP DSLAM provides 48 ADSL port connections, plus built-in ADSL/POTS splitter per port (48 ADSL ports via 2 RJ-21 (Telco-50) connectors, plus 48 splitter ports through 2 other RJ-21 (Telco-50) connectors). A 1000BASE-T or 1000BASE-LX Gigabit uplink connects the DAS-3248 to the carrier's network.

VLAN Support for Enhanced Security

The DAS-3248 IP-DSLAM supports 802.1Q Tagged VLAN to provide complete subscriber isolation and enhance the ADSL network performance.

Versatile Management

Up to 8 DAS-3248 can be cascaded and managed as one single unit. With the local RS-232 and Ethernet management port, plus inband SNMP/TELNET channel, the DAS-3248 provides local and remote management capabilities using a Command Line Interface (CLI), SNMP and Telnet. In addition, a Microsoft NT/SNMP based GUI EMS system provides service providers with low-cost, high-value central management capability of the DAS-3248.

Complete ADSL Solution

With the DAS-3248 IP-DSLAM, D-Link provides service providers with a complete ADSL service solution. This IP DSLAM integrates and operates seamlessly with D-Link's extensive range of ADSL modems and routers Customer Premise Equipment (CPE).

Product Function & Features

Cost Saving Solution for Service Providers

- 48 ADSL/ADSL2/ADSL2+ subscriber interface ports
- 1000BASE-T and fiber Gigabit uplinks to carriers' backbones
- Built in POTS splitter per port
- Easy expansion: low-profile rack-mount boxes can be cascaded to maximum 8 units and managed as one single entity

Flexible and Secure Configuration/Management

- Microsoft NT/SNMP-based GUI EMS
- Local RS-232 out-of-band CLI and remote in-band SNMP/TELNET management
- 3-levels of user privilege system management
- SNMP v1, v2c, v3 support
- Firmware upload/download via FTP or TFTP

Advanced Functions for Broadband Service Offering

- IGMP snooping
- Up to 8 VCs, 128 MAC addresses per DSL port
- Up to 64 x 128 MAC addresses, 2K Multicast MAC addresses per DAS-3248 device
- Up to 512 VLANs (any value in 4096)
- Static VLAN and port-based VLAN support
- Configurable packet size (64 to 1536 bytes)
- Security functions: VLAN filtering, MAC filtering, IP filtering, MAC-based and IP-based Access Control List (ACL)
- 802.1d Spanning Tree for redundant backup bridge paths
- 802.1p traffic prioritization for QoS
- MAC-based and IP-based rate limiting
- 802.3ad link aggregation
- BRAS, 802.1x, DHCP server/relay, PPPoE, MPLS, VLAN-based VPN, L3 router, L2TP *

* Functions available in future firmware upgrade.

DAS-3248/DAS-3248F

Technical Specifications

ADSL

Device Ports

- 48 ADSL/ADSL2/ADS2+ ports (2 RJ-21 Telco-50 connectors)
- 48 splitter ports (2 RJ-21 Telco-50 connectors)
- 2 10/100/1000BASE-T copper Gigabit ports (DAS-3248)
- 1 10/100/1000BASE-T copper Gigabit port, 1 1000BASE-LX fiber Gigabit port supporting max. 10 km single-mode fiber cable distance (DAS-3248F)
- 1 10/100BASE-TX Ethernet port
- 1 RS-232 console port

Protocol Handling Capability

- 8 VCs per DSL port
- 128 MAC addresses per DSL port
- 2K Multicast MAC addresses
- 512 VLAN (any value in 4096)
- Configurable packet size: 64 bits to 1542 bits

ATM MIBs

RFC 1514, 2515 Definitions of Managed Objects for ATM Management

ADSL/ADSL2/ADSL2+ Interface

- Downstream DMT data rate from 32Kbps to 10.5Mbps
- Upstream DMT data rate from 32Kbps to 1Mbps
- Standard compliance: ITU G.992.1 (G.DMT), G.DMT.bis, ITU G.992.2 (G.Lite), ANSI T1.413 issue 2, ITU G.994.1 (G.handshake) for ADSL, G.992.3 for ADSL2, G.992.5 for ADSL2+
- Extended power management capability to optimize power consumption for each application
- Maximum cable distance from DSLAM to subscriber CPE: 6.1 km (20,000 feet)

Management

- Microsoft NT/SNMP-based GUI EMS
- Local RS-232 CLI and Ethernet SNMP/Telnet management
- Remote in-band SNMP/Telnet management
- SNMP v.1, v.2c, v.3
- Up to 8 DAS-3248 cascaded units manageable as one single unit

Firmware Upload/Download

Through FTP or TFTP

Private MIBs

D-Link private MIBs

Protocol

STP, IGMP snooping, GMRP, GVRP, LACP, LACP marker, SNMP/UDP/IP/MAC/Ethernet

Diagnostic LEDs

- Power (per device)
- Maintenance (per device)
- Alarm (per device)
- Master (per device)
- 1 to 48 (ADSL ports)

Physical & Environmental

Power Requirement

-42 to -56 VDC

Power Supply

Auto ranging 90 to 250 VAC/50-60 Hz
Internal universal power supply

Power Consumption

150 watts (max.)

Dimension

440 (W) x 400 (D) x 44 (H) mm (device only)
19-inch standard rack-mount width, 1 U height

Weight

6.8 kg (device only)

Operating Temperature

0° to 50 °C (32° to 122 °F)

Storage Temperature

-30° to 70 °C (22° to 158 °F)

Humidity

5% to 90% RH non-condensing

Emission

- FCC Class A
- CE Class A

Safety

EN60950



Ordering Information

DAS-3248	48-Port IP DSLAM (With 2 1000BASE-T Gigabit uplinks)
DAS-3248F	48-Port IP DSLAM (With 1 1000BASE-T and 1 1000BASE-LX Gigabit uplink)

D-Link®

Specifications subject to change without prior notice.
D-Link is a registered trademark of D-Link Corporation/D-Link System Inc. All other trademarks belong to their proprietors.

U.S.A

Canada

Europe (U. K.)

Germany

France

Netherlands

Belgium

Italy

Sweden

Denmark

Norway

Finland

Spain

Portugal

Czech Republic

Switzerland

Greece

Luxemburg

Poland

Hungary

Singapore

Australia

India

Middle East (Dubai)

Turkey

Egypt

Israel

LatinAmerica

Brazil

South Africa

Russia

China

Taiwan

Headquarters

TEL: 1-800-326-1688

TEL: 1-905-8295033

TEL: 44-20-8731-5555

TEL: 49-6196-77990

TEL: 33-1-30238688

TEL: 31-10-282-1445

TEL: 32(0)2-517-7111

TEL: 39-02-2900-0676

TEL: 46-(0)8564-61900

TEL: 45-43-969040

TEL: 47-23-897189

TEL: 358-9-2707 5080

TEL: 34-93-4090770

TEL: 351-21-8688493

TEL: 420-(603)-276-589

TEL: 41-(0)-1-832-11-00

TEL: 30-210-9914 512

TEL: 32-(0)2-517-7111

TEL: 48-(0)-22-583-92-75

TEL: 36-(0)-1-461-30-00

TEL: 65-6774-6233

TEL: 61-2-8899-1800

TEL: 91-022-26526696

TEL: 971-4-3916480

TEL: 90-212-289-56-59

TEL: 202-414-4295

TEL: 972-9-9715700

TEL: 56-2-232-3185

TEL: 55-11-550-39320

TEL: 27-12-665-2165

TEL: 7-095-744-0099

TEL: 86-10-58635800

TEL: 886-2-2910-2626

TEL: 886-2-2916-1600

FAX: 1-866-743-4905

FAX: 1-905-8295223

FAX: 44-20-8731-5511

FAX: 49-6196-7799300

FAX: 33-1-30238689

FAX: 31-10-282-1331

FAX: 32(0)2-517-6500

FAX: 39-02-2900-1723

FAX: 46-(0)8564-61901

FAX: 45-43-424347

FAX: 47-22-309085

FAX: 358-9-2707-5081

FAX: 34-93-4910795

FAX: 41(0)-1-832-11-01

FAX: 30-210-9916902

FAX: 32-(0)2-517-6500

FAX: 48-(0)-22-583-92-76

FAX: 36-(0)-1-461-30-09

FAX: 65-6774-6322

FAX: 61-2-8899-1868

FAX: 91-022-26528914

FAX: 971-4-3908881

FAX: 90-212-289-76-06

FAX: 202-415-6704

FAX: 972-9-9715601

FAX: 56-2-232-0923

FAX: 55-11-550-39322

FAX: 27-12-665-2186

FAX: 7-095-744-0099 #350

FAX: 86-10-58635799

FAX: 886-2-2910-1515

FAX: 886-2-2914-6299