



— DCS-5300G

Pan/Tilt High-Speed Wireless Internet Camera

With High-Quality CCD Sensor, Digital Zoom & 802.11g WLAN

The DCS-5300G Internet Camera is an advanced security system that allows you to watch and listen remotely. This full-featured camera connects to an Ethernet network in a building or campus, to broadband Internet as well as to a wireless local area network (WLAN). It provides you with high-quality video and audio. Equipped with built-in Web server, a micro-phone for listening, and a motor for rotation, this camera can be panned and tilted remotely, accessed and controlled from any PC/notebook over a local network or through the Internet. With motion detected image recording, time-saving trigger event playback, alert message and powerful software for multi-camera monitoring and management, this camera provides a comprehensive system for convenient surveillance from both a local site or remotely from anywhere in the world.

Stand-alone System With Integrated Web Server

This Internet Camera comes with a built-in CPU and Web server, providing a low-cost solution for security needs. Its integrated Web server eliminates the need to connect the camera to a computer. Once installed, you use the built-in IP address to gain access to the camera, view live streaming video, and make changes to camera settings.

Web-based Remote Access

You can install your camera at home then view the images from anywhere in the world on a computer running Internet Explorer. Directly connected to the Internet without going through any computer, this camera is simple to install and easily integrates with your network environment.

Automatic Camera Movement to View Different Angles

The camera is mounted on a motor for rotation to capture images from different angles. From a remote site, you can manually rotate the camera's horizontal and vertical movements. The camera movement angles can also be set up for automatic panning and tilting in rotation according a pre-set timing.

Multi-Camera Monitoring

Surveillance software is included to let you view up to 16 cameras on a single computer screen at one central location. Images can be recorded to your computer's hard drive manually or according to a pre-set schedule. The camera can be connected to external alarms and sensors, and you can set up automated email alerts for sending through the Internet to alarm you instantly of all unusual happenings.

Motion Detected Recording

Instead of recording 24 hours a day, 7 days a week, images can also be recorded only when motions are detected. This saves disk space and eliminates the time wasted to view unnecessary images. Images can be directly archived straight to your computer hard drive or to a Network Attached Storage. Playback consumes little time with triggered event browsing and fast database searching.

High-Quality Video & Sound

This camera uses MPEG-4 Short Header Mode to stream live video at up to 30 frames per second for real-time viewing. A CCD sensor provides sharp video images with lifelike color representation. The camera also features 4x digital zoom for close-up viewing using the Web interface. Plus, with low light sensitivity, it has the capability to monitor and record video in rooms with minimal lighting, making it ideal to use at night.

A built-in microphone allows you to listen while watching live images. The camera can also be attached to an external, more powerful microphone and a TV in a private room, where you can monitor streaming images and listen to surveillance sound.

Wireless and Ethernet Connection

For effective surveillance in and around a building, this camera comes with a built-in high-speed 802.11g wireless network interface, allowing images to be transmitted at up to 54Mbps wireless speed. In addition, a 10/100BASE-TX Ethernet port is also provided for convenient connection to an Ethernet network or to a broadband Internet via a home gateway router.

Key Features

- Stand-alone Internet camera with CPU & RAM, no need to attach to PC
- Built-in rotation motor for manual or auto camera pan/tilt with wide movement angle support
- 4x digital zoom for close-up viewing
- Sound surveillance through built-in microphone or powerful external microphone connected to MIC jack
- Simple to use with real-time monitoring in Windows environment
- Local access through high-speed 802.11g wireless LAN and Ethernet
- Remote access from web browser
- Supports DDNS and UPnP for easy configuration in a network environment
- Surveillance software to control up to 16 cameras
- Motion detection triggered recording or scheduled recording to administrator's hard disk or Network Attached Storage (and VCR) for each camera
- Smart playback with triggered event browsing, fast database searching
- Auto alarm in different ways
- AV cable connection local TV for video/audio monitoring
- MPEG4 short header mode high compression ratio
- Connects to external devices for alarm-based event recording when trigger is activated
- Implemented for intruder detection with still image capture & e-mail notice
- Powerful software for image capture & video recording
- Web-based configuration, remote utility provided

DCS-5300G

Technical Specifications

Internet Camera

Hardware

- Sensor: 1/4-inch color CCD sensor, interlace scan mode, supports 380 TV lines video output, up to 30 frames per second
- Pan range +/- 135 degrees
- Tilt range +90 to -45 degrees
- Automatic Gain control (AGC) 24dBi
- Automatic Exposure (AE)
- Automatic White Balance
- Electronics shutter 1/60 to 1/15000 second
- Minimum illumination 1.0lux @ F2.0
- Lens mounting: board lens, 4.3mm, F2.0

Image

- 24-bit RGB, 4CIF, supports up to 704 x 480 (NTSC)/704 x 576 (PAL) resolution
- MPEG4 short header mode compression
- Compression ratio: 5 levels
- Adjustable image size, quality and bit-rate
- Time stamp and text overlay

Audio

24kbps

Video Sizes

QCIF (30 fps), CIF (30 fps), 4CIF (10 fps) (user-selectable)

Digital Zoom *

Up to 4x magnification

* 4x digital zoom enlarges an image by magnifying the pixels in a selected portion of the image by 4 times.

Communication

- 1 RJ-45 auto-sensing 10/100BASE-TX port to connect to 10/100Mbps Ethernet
- Supported communication protocols: HTTP, FTP, TCP/IP, UDP, SMTP, DHCP, Telnet, NTP, DDNS, UPnP and DNS

Viewing System Requirement

Internet Explorer 5.x or above

Security

- Administrator and user group protected
- 15 digits password authentication

LED Indicators

- System power indicator
- Network activity indicator

Alarms and I/O

- Motion detection (activity detection)
- Periodical image transfers through e-mail and upload to a server, using FTP
- 1 sensor input (12Vdc to 48Vdc/50mA)
- 1 relay output (Max. 24Vdc/1A, 125Vac/0.5A)

Management and Software Update

- Configuration and system log can be accessed via Web browser and FTP application remotely
- Allows new firmware version updates via TCP/IP network

Application Channel Display (6 layouts)

Maximum 16 views

Recording Modes

- Manual Control
- Event-driven
- Scheduled recording

Playback Schemes

Date, Time interval, and event triggering with preview for every camera

Playback Control Modes

Play, Stop, Pause, Fast Forward, Slow Forward, Pull-bar, Zoom in, Zoom out

Built-in Wireless LAN

Wireless LAN Standards

- 802.11g
- 802.11b

Radio and Modulation Schemes

- 802.11b: DQPSK, DBPSK and CCK
- 802.11g: BPSK, QPSK, 16QAM, 64QAM, OFDM

Operating Frequency

2400 to 2483.5MHz

Wireless Data Rates

- 802.11b: 11, 5.5, 2 and 1Mbps
- 802.11g: 54, 48, 36, 24, 18, 12, 9 and 6Mbps

Receiver Sensitivity

- 802.11b:
 - 11 Mbps (CCK): -84dBm
 - 5.5 Mbps (CCK): -86dBm
 - 2 Mbps (DQPSK): -88dBm
 - 1 Mbps (DBPSK): -90dBm(typically @PER < 8% packet size 1024 and @ 25° C + 5° C)

- 802.11g:
 - 54 Mbps (OFDM): -66dbm
 - 48 Mbps (OFDM): -70dbm
 - 36 Mbps (OFDM): -76dbm
 - 24 Mbps (OFDM): -79dbm
 - 18 Mbps (OFDM): -83dbm
 - 12 Mbps (OFDM): -85dbm
 - 9 Mbps (OFDM): -86dbm
 - 6 Mbps (OFDM): -86dbm(typically @PER < 10% packet size 1024 and @ 25° C + 5° C)

Transmitter Output Power

- 802.11b: 16dBm (typical)
- 802.11g: 12dbm (typical)

Antennas

2dBi Gain dipole antenna with reverse SMA plug

Security

WEP 64/128-bit data encryption (user-selectable)

Physical & Environmental

Power

- Through switching external power adapter (AC input range 100 to 240 V, 50/60Hz)
- DC Output: 12VDC, 1.5A

Dimensions

110.5mm (H) x 103.5mm (W) x 99mm(D) (camera only, mounted motor included)

Weight

395 grams (camera only, mounted motor included)

Operation Temperature

0° to 40° C (32° to 104° F)

Storage Temperature

-20° to 70° C (-4° to 158° F)

Humidity²

20% to 80% RH non-condensing

Emission (EMI)

- FCC Class B
- CE Class B

Safety

LVD (En60950)

DCS-5300G

Technical Specifications

Internet Camera

Box Includes

- DCS-5300G Internet Camera
- Remote control
- A/V cable
- Cat. 5 Ethernet cable
- Manual & Software on CD-ROM
- Stand & Mounting Brackets
- AC power adapter
- Quick Installation Guide



D-Link Worldwide Offices

U.S.A	TEL: 1-800-326-1688	FAX: 1-866-743-4905	Bulgaria	TEL: 359 2 958 22 42	FAX: 359 2 958 65 57
Canada	TEL: 1-905-8295033	FAX: 1-905-8295223	Romania	TEL: 40(0)21 320 23 05	FAX: 40(0)21 320 23 07
Europe (U. K.)	TEL: 44-(0)20-8955-9000	FAX: 44-(0)20-8955-9001	Singapore	TEL: 65-6774-6233	FAX: 65-6774-63225
Germany	TEL: 49-(0)6196-77990	FAX: 49-(0)6196-7799300	Australia	TEL: 61-2-8899-1800	FAX: 61-2-8899-1868
France	TEL: 33 (0)1 30 23 86 88	FAX: 33 (0)1 30 23 86 89	India	TEL: 91-22-2652 6696	FAX: 91-22-2652 8914
Netherlands	TEL: 31-(0)10-282-1445	FAX: 31-(0)10-282-1331	Middle East (Dubai)	TEL: 971-4-391-6480	FAX: 971-4-390-8881
Belgium & Luxemburg	TEL: 32(0)2 517 7111	FAX: 32(0)2 517 6500	Egypt	TEL: 202-291-9035	FAX: 202-291-9051
Switzerland	TEL: 41 (0)1 832 11 00	FAX: 41 (0)1 832 11 01	Turkey	TEL: 90-212-289-5659	FAX: 90-212-289-7606
Austria	TEL: 43 (0)1 240 27 270	FAX: 43 (0)1 240 27 271	Iran	TEL: 90-212-289-5659	FAX: 90-212-289-7606
Sweden	TEL: 46-(0)8 564 619 00	FAX: 46-(0)8 564 619 01	Pakistan	TEL: 92-21-454-8158	FAX: 92-21-453-5103
Denmark	TEL: 45-43-969040	FAX: 45-43-424347	Israel	TEL: 972-9-9715700	FAX: 972-9-9715601
Norway	TEL: 47 99 300 100	FAX: 47 22 30 90 85	Latin America	TEL: 56-2-5838-950	FAX: 56-2-5838953
Finland	TEL: 358-10 309 8840	FAX: 358-10 309 8841	Brazil	TEL: 55-11-2185-9300	FAX: 55-11-2185-9322
Italy	TEL: 39-02-2900-0676	FAX: 39-02-2900-1723	South Africa	TEL: 27-12-665-2165	FAX: 27-12-665-2186
Spain	TEL: 34 93 409 0770	FAX: 34 93 491 0795	Russia	TEL: 7-495-744-0099	FAX: 7-495-744-0099
Portugal	TEL: 351 21 8688493	FAX: 351 21 8622492	Japan	TEL: 81-3-5781-0963	FAX: 81-3-5781-0965
Greece	TEL: 30 210 9914 512	FAX: 30 210 9916902	Korea	TEL: 82-2-890-5491	FAX: 82-2-890-549
Czech Republic	TEL: 420 224 247 500	FAX: 420 224 234 967	China	TEL: 86-10-58635800	FAX: 86-10-58635799
Hungary	TEL: 36 (0)1 461 30 00	FAX: 36 (0)1 461 30 04	Taiwan	TEL: 886-2-6600-0123	FAX: 886-2-6600-3939
Poland	TEL: 48 (0)22 583 92 75	FAX: 48 (0)22 583 92 76	Headquarters	TEL: 886-2-6600-0123	FAX: 886-2-6600-9898