



## Cable/DSL VPN Router With Built-in 8-Port Switch

The DI-808HV is a high-performance broadband router with secure data transmission designed for branch office communication. Cost-effectively linking an office to the outside world through the Internet, this router offers an alternative to the cost-prohibitive point-to-point dedicated connectivity of leased lines. This router provides IPSec security for Virtual Private Network applications, enabling you to extend your branch network to remote networks, such as your corporate office or a trusted supplier, to act as if the two are a single LAN.

### Secure Transmission Over the Internet

The DI-808HV prevents your confidential data from being accessed and tampered with when traveling along the public Internet to your destinations. VPN services include pass-through of multiple concurrent IPSec and PPTP VPN sessions for telecommuters to transmit sensitive information. Through VPN tunneling protocols, the router can privatize your communication channels. You can safely exchange mail and data with your head office over the Internet, without fear of observation, modification, or spoofing.

### IPSec and Multi-Level VPN Services

With support for up to 40 IPSec tunnels, the router can provide flexible VPN implementation for data confidentiality, integrity and origin authentication to 40 remote sites and telecommuters. Supported data encapsulation, encryption and authentication options include IP ESP, DES, 3DES, MD5 and SHA-1. This enables you to carry out applications such as virtual private networks, including Intranets, Extranets, and remote user access.

### Hardware Acceleration

The router uses a special design ASIC to perform VPN encryption and decryption. This off-loads CPU loading through hardware-based acceleration.

### Firewall Protection

The router provides firewall security using Stateful Packet Inspection (SPI) and hacker attack logging for Denial of Service (DoS) attack protection. SPI inspects the contents of all incoming packet headers before deciding what packets are allowed to pass through. Filters can be set based on MAC address, IP address, URL and/or domain name.

### Virtual Server and DMZ Support

The router also blocks and re-directs certain ports to limit the services that outside users can access on your network. Virtual Server Mapping is used to re-task services to multiple servers. The router can be set to allow separate FTP, Web, and Multiplayer game servers to share the same Internet-visible IP address while still protecting your servers and workstations from hackers.

You can configure any of the built-in LAN ports of the router to function as a DMZ port. A DMZ setting can be applied to a single client (such as a Web server) behind the DI-808HV to fully expose it to the Internet and ensure complete Internet application compatibility even if the specific port is not known. This allows you to set up web sites and e-commerce applications from your office while maintaining protection for the rest of your office LAN.

### 8 Switch Ports for Ready LAN Connection

With 8 built-in Ethernet switch ports supporting 10/100Mbps network speeds and auto MDI/MDIX plug-and-play, the router provides ready connection for workstations and servers, saving you the cost and trouble of installing a separate LAN switch.

### UPnP Enabled for Compatibility

The router is designed for easy and robust connectivity among heterogeneous standards-based network devices. Computers can communicate directly with the router for automatic opening and closing of UDP/TCP ports to take full advantage of security provided without sacrificing functionality of on-line applications such as video conferencing.

## Key Features

- 168-bit 3DES IPSec advanced VPN security
- 3DES with SHA-1 advanced secure configuration
- Up to 40 VPN tunnels to 40 remote sites
- DoS, SPI, packet filtering firewall protection
- 10/100BASE-TX port for DSL/cable modem connection
- Additional RS-232 COM port for ISDN or 56Kbps analog modem backup supporting dial-on-demand & idle timer auto-disconnection
- 8 10/100BASE-TX switch ports for 8 workstation/server connections
- Aggressive/main client mold for VPN
- Web-based configuration setup
- Enabled NetBIOS broadcast
- Dynamic DNS support
- SDI Service (Home Internet Solution) port
- Universal Plug-n-Play (UPnP) enabled

# DI-808HV

## Technical Specifications

### Hardware

#### WAN Ports

- 1 10/100BASE-TX port for DSL/cable modem connection
- 1 RS-232 port (460Kbps Baud) for ISDN TA/analog modem connection (for WAN backup)

#### LAN Ports

- 8 10/100BASE-TX switch ports with auto MDI/MDIX support

#### Broadband Support

- DSL modem
- Cable modem
- PPP over Ethernet (PPPoE)

#### Backup Link Support

- Dial-up ISDN TA
- Dial-up Analog modem
- PPP
- Dial-on-Demand with auto login to ISP
- Auto-disconnect with user-defined idle timer
- PAP/CHAP security

#### Diagnostic LEDs

- Power
- Status
- WAN Port (Link/Act)
- COM Port
- 8 LAN Ports (Link/Act)

### Routing

#### Routed Packet Type

IP packets

#### Routing Protocols & Methods

- RIP-1, RIP-2
- Static Routing
- Dynamic Routing

### VPN & IPSec

#### Application Support

- IPSec pass-through
- PPTP pass-through
- L2TP pass-through

#### Data Encryption Methods

- IP ESP (Encapsulating Security Payload)  
Confidentiality over IP payload  
Optional authentication of IP payload and ESP header
- Null encryption

#### Encryption Transforms

- 56-bit DES (Data Encryption Standard)
- 168-bit 3DES

#### Authentication Transforms (for ESP and AH)

- MD5
- SHA-1

#### Security

- Pre-shared key
- Manual key
- IKE Security Association (SA) assignment

#### Connection Modes

- Site to Site
- Client to Site

#### Number of Tunnels

40 IPSec tunnels (max.)

### Internet Gateway & Firewall

#### Supported Functions

- Network Address Translation (NAT)
- DHCP server automatic IP assignment
- Virtual server

#### Packet Inspection

Static Packet Inspection (SPI)

#### Number of DMZ Ports

1 port (user-assignable to any LAN port)

#### Firewall Security

- Stateful Packet Inspection (SPI) to prevent Denial of Service (DoS) attacks (Syn flood, ICMP flood, UDP flood, "ping of death", IP spoofing, land attack, tear drop attack, IP address sweep attack, Win Nuke attack)
- Intrusion Detection Logging
- LAN/WAN filtering

## Broadband VPN Router

### Management & Configuration

#### IP Number Self-identification

Through DHCP client

#### Local & Remote Management

Web-based utilities (via browser)

#### Firmware Upgrade

Web-based (via browser)

### Physical & Environmental

#### Power Supply

- DC 5V 2A
- Through external power adapter

#### Dimensions

235 x 162 x 35 mm (device only)  
(7.56 x 4.64 x 1.22 inches)

#### Weight

310 grams (0.68 lb.) (device only)

#### Operating Temperature

5 ° to 55 °C

#### Storage Temperature

-20 ° to 70 °C

#### Humidity

10% to 90% non-condensing

#### EMI Certification

- FCC Class B
- CE Class B

#### Safety

UL



## Ordering Information

### Broadband VPN Router With Built-in 8-Port Switch

**DI-808HV** 1 10/100BASE-TX port (for DSL/cable modem connection)  
1 RS-232 COM port (for ISDN TA/analog modem connection)  
8 10/100BASE-TX switch ports

Please specify one of the following after the model number:

**DI-808HV/A** Includes US standard power adapter  
**DI-808HV/E** Includes EU standard power adapter  
**DI-808HV/B** Includes UK standard power adapter  
**DI-808HV/N** Includes Australia standard power adapter

# D-Link®

Specifications subject to change without prior notice.  
D-Link is a registered trademark and Express EtherNetwork is a trademark of D-Link Corporation/D-Link System Inc. All other trademarks belong to their proprietors.

<b>U.S.A</b>	TEL: 1-949-788-0805	FAX: 1-949-753-7033
<b>Canada</b>	TEL: 1-905-8295033	FAX: 1-905-8295095
<b>Europe</b>	TEL: 44-20-8731-5555	FAX: 44-20-8731-5511
<b>Germany</b>	TEL: 49-6196-77990	FAX: 49-6196-7799300
<b>France</b>	TEL: 33-1-30238688	FAX: 33-1-30238689
<b>Benelux</b>	TEL: 31-10-282-1445	FAX: 31-10-282-1331
<b>Italy</b>	TEL: 39-2-2900-0676	FAX: 39-2-2900-1723
<b>Iberia</b>	TEL: 34-93-4090770	FAX: 34-93-4910795
<b>Sweden</b>	TEL: 46-(0)8564-61900	FAX: 46-(0)8564-61901
<b>Norway</b>	TEL: 47-22-309075	FAX: 47-22-309085
<b>Denmark</b>	TEL: 45-43-969040	FAX: 45-43-424347
<b>Finland</b>	TEL: 358-9-2707-5080	FAX: 358-9-2707-5081
<b>Singapore</b>	TEL: 65-6774-6233	FAX: 65-6774-6322
<b>Australia</b>	TEL: 61-2-8899-1800	FAX: 61-2-8899-1868
<b>Japan</b>	TEL: 81-3-5434-9678	FAX: 81-3-5434-9868
<b>China</b>	TEL: 86-10-8518-2533	FAX: 86-10-8518-2250
<b>India</b>	TEL: 91-22-652-6696	FAX: 91-22-652-8914
<b>Middle East</b>	TEL: 9714-8834234	FAX: 9714-8834394
<b>Turkey</b>	TEL: 90-212-335-2553	FAX: 90-212-335-2500
<b>Chile</b>	TEL: 56-2-232-3185	FAX: 56-2-232-0923
<b>Brasil</b>	TEL: 55-11-3094-2910	FAX: 55-11-3094-2921
<b>South Africa</b>	TEL: 27(0)1266-52165	FAX: 27(0)1266-52186
<b>Russia</b>	TEL: 7-095-737-3389	FAX: 7-095-737-3390
<b>Taiwan</b>	TEL: 886-2-2910-2626	FAX: 886-2-2910-1515
<b>D-Link Corp.</b>	TEL: 886-2-2916-1600	FAX: 886-2-2914-6299



RECYCLABLE  
Rev. 01 (Oct. 2003)