

ADSL2/+ Router

With Firewall Protection/QoS Control

- Share High-Speed ADSL2/+ Connection Among Group of Computers
- DoS & SPI Firewall Protection
- QoS & SNMP Management Support

FEATURES

LAN Interface

- 10/100BASE-TX Ethernet Port

High-Speed ADSL Access

- ADSL: G.992.1 G.dmt, G.992.2 G.lite, ANSI T1.413 Issue 2 (Full Rate DMT Over Analog POTS) Annex A
- ADSL2: G.992.3 (G.dmt.bis) Annex A
- ADSL2+: G.992.5 Annex A
- G.994.1 G.hs Auto-Negotiation of Different ADSL Flavors

Firewall/Access Security

- DoS Attack Prevention
- Stateful Packet Inspection (SPI)
- IP/MAC-Based Packet Filtering
- Port-Based VLAN

QoS/Bandwidth Control

- Traffic Prioritization
- IGMP Snooping Multicast

Easy Setup/Flexible Management

- Dynamic Domain Name System (DDNS)
- Universal Plug and Play (UPnP) Compliant
- Quick Installation Wizard
- Web-Based GUI for Local/Remote Management
- SNMP Management

Remote Management

- TR-069 (optional)

The DSL-520T ADSL2/+ router is a versatile, high-speed remote router for home and the small office. With integrated ADSL2/2+ supporting up to 24Mbps download speed, firewall protection, Quality of Service (QoS), this router provides all the functions that a home or small office needs to establish a secure and high-speed remote link to the outside world.

High-Speed ADSL Connection. The DSL-520T features the latest ADSL2/+ standards, providing speeds of up to 24Mbps downstream and 1Mbps upstream (ADSL2+), or 12Mbps downstream and 1Mbps upstream (ADSL2). This router auto-senses the connection type and auto-negotiates the best modulation scheme, using the G.hs (handshake) protocol.

Shared Internet Access for Workgroup. The DSL-520T provides DHCP server for a group of home or small office users to simultaneously access the Internet. It provides an Ethernet port that can be connected to a group of users through an Ethernet switch.

Firewall Protection. The DSL-520T provides firewall security using Stateful Packet Inspection (SPI) and hacker attack logging for Denial of Service (DoS) attack protection. SPI inspects the contents of all incoming packet headers before deciding what packets are allowed to pass through. Access control is provided with packet filtering based on port and source/destination MAC/IP addresses. With Virtual Server Mapping, the router can be set to allow separate FTP, Web, and multiple games to share the same Internet-visible IP address while still protecting your servers and workstations from hackers. VPN pass-through is provided to let mobile users access files and mail from offices to work at home without having to use complex VPN client software.

Quality of Service Features. The DSL-520T supports priority queues to enable a group of home or office users to experience the benefit of smooth network connection of inbound and outbound data without concern of traffic congestion. This QoS support allows you to enjoy high ADSL transmission for applications such as VoIP, multimedia and on-line games over the Internet.



Technical Specifications

Hardware

Interfaces

- 1 RJ-11 ADSL port
- 1 RJ-45 10/100BASE-TX Fast Ethernet Port with auto MDI/MDIX
- Factory reset button

ADSL

Standards

- ADSL standards: ANSI T1.413 Issue 2, ITU G.992.1 (G.dmt) Annex A, ITU G.992.2 (G.lite) Annex A
- ADSL2 standards: ITU G.992.3 (G.dmt.bis) Annex A, ITU G.992.4 (G.lite.bis) Annex A
- ADSL2+ standards: ITU G.992.5 Annex A
- Auto-handshake: ITU G.994.1 (G.hs)

Data Rates

- G.dmt: 8Mbps downstream, 832Kbps upstream
- G.lite: 1.5Mbps downstream, 512Kbps upstream
- ADSL2: 12Mbps downstream, 1Mbps upstream
- ADSL2+: 24Mbps downstream, 1Mbps upstream

ATM & PPP Protocols

- ATM Adaptation Layer Type 5 (AAL5)
- Bridged or routed Ethernet encapsulation
- VC and LLC based multiplexing
- PPP over Ethernet (PPPoE)
- PPP over ATM (RFC 2364)
- Classical IP over ATM (RFC 1577)
- OAM F4/F5

Router

Network Protocols & Features

- NAT, Static Routing, RIP v.1, v.2
- Universal Plug and Play (UPnP) Compliant
- Dynamic Domain Name System (DDNS)
- Virtual Server & DMZ
- SNTP, IGMP proxy

Firewall/Access Security

- Built-in NAT firewall
- Stateful Packet Inspection (SPI)
- DoS attacks prevention (IP Spoofing, Land Attack, Smurf Attack, Ping of Death, TCP SYN flooding)
- Packet filtering based on port, source IP address, destination IP address, MAC address (ICMP/TCP/UDP)

Virtual Private Network (VPN)

- PPTP/IPSec pass-through

Configuration/Management

- Quick Installation Wizard
- Web-based GUI for remote/local management
- Firmware upgrade, configuration data upload/download via Web-based GUI
- Telnet server for remote/local management
- Syslog monitoring
- SNMP v.1, v.2c support using built-in MIB-II(RFC-1213)
- DHCP server/client

QoS Control

- LAN to WAN traffic prioritization/bandwidth management
- 802.1p traffic prioritization

Security/Bandwidth Management

- IGMP Snooping with 32 Multicast groups
- PVC/VLAN port mapping (4 VLANs)
- Bandwidth management based-on IP protocol, port number, MAC address

Physical & Environmental

Power Input

- Through 9VAC 1A external power adapter (without dying gasp)
- Through 12VAC 1.2A external power adapter (with dying gasp)

Power Consumption

- 9 watts (without dying gasp)
- 12 watts (with dying gasp)

Dimensions

142 x 117 x 31 mm

Weight

198 grams (approx.)

Operating Temperature

0° to 40°C

Storage Temperature

-20° to 70°C

Operating Humidity

5% to 95% non-condensing

Emission (EMC/EMI)

- FCC Part 15 Class B
- CE (EN55022/EN55024/EN300 328/EN301 489)

Safety

- CSA
- LVD



D-Link Worldwide Offices

U.S.A.

TEL: 1-800-326-1688

FAX: 1-866-743-4905

Canada

TEL: 1-905-8295033

FAX: 1-905-8295223

Europe (U. K.)

TEL: 44-20-8731-5555

FAX: 44-20-8731-5511

Germany

TEL: 49-6196-77990

FAX: 49-6196-7799300

France

TEL: 33-1-30238688

FAX: 33-1-30238689

Netherlands

TEL: 31-10-282-1445

FAX: 31-10-282-1331

Belgium

TEL: 32(0)2-517-7111

FAX: 32(0)2-517-6500

Italy

TEL: 39-02-2900-0676

FAX: 39-02-2900-1723

Sweden

TEL: 46-(0)8564-61900

FAX: 46-(0)8564-61901

Denmark

TEL: 45-43-969040

FAX: 45-43-424347

Norway

TEL: 47-99-300-100

FAX: 47-22-309580

Finland

TEL: 358-9-2707 5080

FAX: 358-9-2707-5081

Spain

TEL: 34-93-4090770

FAX: 34-93-4910795

Portugal

TEL: 351-21-8688493

FAX: 351-21-8688493

Czech Republic

TEL: 420-(603)-276-589

FAX: 420-(603)-276-589

Switzerland

TEL: 41-(0)-1-832-11-00

FAX: 41(0)-1-832-11-01

Greece

TEL: 30-210-9914 512

FAX: 30-210-9916902

Luxemburg

TEL: 32-(0)2-517-7111

FAX: 32-(0)2-517-6500

Poland

TEL: 48-(0)-22-583-92-75

FAX: 48-(0)-22-583-92-76

Hungary

TEL: 36-(0)-1-461-30-00

FAX: 36-(0)-1-461-30-09

Singapore

TEL: 65-6774-6233

FAX: 65-6774-6322

Australia

TEL: 61-2-8899-1800

FAX: 61-2-8899-1868

India

TEL: 91-022-26526696

FAX: 91-022-26528914

Middle East (Dubai)

TEL: 971-4-3916480

FAX: 971-4-3908881

Turkey

TEL: 90-212-289-56-59

FAX: 90-212-289-76-06

Egypt

TEL: 202-414-4295

FAX: 202-415-6704

Israel

TEL: 972-9-9715700

FAX: 972-9-9715601

Latin America

TEL: 56-2-232-3185

FAX: 56-2-232-0923

Brazil

TEL: 55-11-218-59300

FAX: 55-11-218-59322

South Africa

TEL: 27-12-665-2165

FAX: 27-12-665-2186

Russia

TEL: 7-095-744-0099

FAX: 7-095-744-0099 #350

China

TEL: 86-10-58635800

FAX: 86-10-58635799

Taiwan

TEL: 886-2-6600-0123

FAX: 886-2-6600-1188

Headquarters

TEL: 886-2-2916-1600

FAX: 886-2-2914-6299