

AirPremier AG™ Dualband



— DWL-AG660

802.11a/g Tri-Mode Dualband Wireless CardBus Adapter

The D-Link AirPremierAG™ DWL-AG660 wireless CardBus adapter is a high-performance, versatile and necessary PC networking solution for companies that need to quickly expand or reconfigure their wireless networks as their organization grows. This tri-mode, dualband network card inserts into your notebook/laptop PC to provide you a versatile way to wirelessly connect to any one of three available wireless networks -- 802.11b and the newer, faster 802.11g and 802.11a that operate in two discrete, non-interfering frequency bands, 2.4GHz and 5GHz.

Easiest Way to Expand

If you're a network administrator, the versatile 802.11a/b/g-compatible DWL-AG660 adapter gives you an immediate way to expand your existing 802.11b network and protect your overall wireless network investment. By installing DWL-AG660 network adapters in computers throughout your organization, your employees can access wireless Access Points and routers from their PCs. And as your company expands or reorganizes, you won't have to keep pulling and plugging Ethernet cables because no matter where the workstation is relocated, it's still connected to the network.

End-to-End Wireless Solution

When you add an 802.11a/b/g access point (D-Link AirPremierAG™ DWL-7100AP) or router (D-Link AirPremierAG™ DI-784) to your wireless network, you will have an end-to-end wireless solution capable of handling up to 15 times the user load of your current 802.11b network.

108Mbps Dualband High Speed

In addition to its compatibility with earlier 802.11b networks, the DWL-AG660 offers the robust speed, up to 108Mbps (Turbo mode), of the newer 802.11g and 802.11a standards, so everyone can work faster and more efficiently. In addition to the 2.4GHz frequency band operated by 802.11b and g, the 5GHz band used by 802.11a also offers a way to quickly transfer data in a frequency range that does not experience interference or interruptions from cordless phones, microwave ovens and other devices utilizing the 2.4GHz frequency.

AES and 802.1x Support

The adapter supports AES enhanced security and 802.1x for user authentication, providing a formidable barrier to hackers and sniffers, allowing users to securely share data over the network.

WPA/WPA2 EAP Support

Enhanced security is provided with Wi-Fi Protected Access (WPA) to authorize and identify users based on a secret key that changes automatically at a regular interval. Used in conjunction with a RADIUS server, WPA/WPA2 employs TKIP (Temporal Key Integrity Protocol) to change the temporal key every 10,000 packets. This insures much greater security than the standard WEP security, which requires the keys to be changed manually. The adapter supports WPA/WPA2-EAP (Extensible Authentication Protocol) for authentication of 802.11 clients using server-side digital certificates. EAP creates an SSL/TLS tunnel between each client and the authentication server, which protects subsequent user authentication exchange.

WPA/WPA2 PSK Support

This function brings a lot of convenience for users who do not incorporate a RADIUS server in their networks. Utilizing the Pre Shared Key (PSK) mode of WPA/WPA2, the adapter gives each user a new security key every time he connects to the network. Users only need to input their encryption information once in the configuration menu. Each user will automatically receive a new key every time he connects, and the inconvenience of manual WEP key input is eliminated.

Key Features

- 802.11a/g industry standard
- Dual 5GHz and 2.4GHz frequency bands
- Up to 108Mbps (Turbo mode) network data transfer rate on both frequency bands, 15 times faster than 802.11b
- Strong 64/128/152-bit WEP data encryption security
- Compatible with existing 802.11b wireless devices
- DFS (Dynamic Frequency Selection)
- Advanced security with WPA/WPA2, 802.1x authentication support
- Powerful integrated antenna provides 100-meter indoor, 400-meter outdoor operation range *
- Runs Windows 98 SE, 2000, ME, XP

* Environmental factors may adversely affect range. 108Mbps Turbo mode operation in 5GHz frequency band not allowed in EU countries.

DWL-AG660

Technical Specifications

5GHz & 2.4GHz Wireless LAN

System Requirements

- Laptop with available CardBus Type II slot
- Windows XP, 2000, ME or 98/SE
- 300MHz CPU or above
- 32MB memory or more

Standards

- IEEE 802.11a
- IEEE 802.11b
- IEEE 802.11g

PC Card Standard & Interface

PC Card Type II CardBus 32-bit compliant

Media Access Control

CSMA/CA with ACK

Data Rates

(With automatic fallback)
54Mbps, 48Mbps, 36Mbps, 24Mbps, 18Mbps, 12Mbps, 11Mbps,
9Mbps, 6Mbps, 5.5Mbps, 2Mbps, 1Mbps

Modulation Technology

- Orthogonal Frequency Division Multiplexing (OFDM)
- Complementary Code Keying (CCK)
- Direct Sequence Spread Spectrum (DSSS)

Frequency Range *

- 2.4GHz to 2.4835GHz
- 5.15GHz to 5.250GHz
- 5.725GHz to 5.850GHz

* Software configurable as allowable frequency will vary from country to country in the European region.

Transmit Output Power

- 802.11a:
 - +10 to 13dBm @ 54Mbps
 - +11 to 14dBm @ 48Mbps
 - +13 to 16dBm @ 36Mbps
 - +15 to 17dBm @ 24, 18, 12, 9 and 6Mbps
- 802.11b:
 - +18dBm @ 11, 5.5, 2, and 1Mbps
- 802.11g:
 - +11 to 15dBm @ 54Mbps
 - +12 to 16dBm @ 48Mbps
 - +13 to 17dBm @ 36Mbps
 - +16 to 18dBm @ 24, 18, 12, 9 and 6Mbps

Receive Sensitivity

- 802.11a (@ 10% PER):
 - 87dBm for 6Mbps
 - 86dBm for 9Mbps
 - 85dBm for 12Mbps
 - 83dBm for 18Mbps
 - 80dBm for 24Mbps
 - 76dBm for 36Mbps
 - 71dBm for 48Mbps
 - 66dBm for 54Mbps
- 802.11b (@ 8% PER):
 - 84dBm for 11Mbps
 - 90dBm for 2Mbps
- 802.11g (@ 10% PER):
 - 87dBm for 6Mbps
 - 86dBm for 9Mbps
 - 85dBm for 12Mbps
 - 83dBm for 18Mbps
 - 80dBm for 24Mbps
 - 76dBm for 36Mbps
 - 71dBm for 48Mbps
 - 66dBm for 54Mbps

Antenna

Internal patch diversity antenna

Operation Range

- Indoors: up to 100 meters *
- Outdoors: up to 400 meters *

* Environmental factors may adversely affect range.

Security

- 64/128/152-bit WEP data encryption
- 802.1x authentication
- 802.11a SSID broadcast (ad hoc mode): disabled
- WPA/WPA2-PSK, and WPA/WPA2-EAP
- Cipher Mode AES and TKIP

Physical & Environmental

LED Indicators

- Activity
- Link

Operating Voltage

3.3 VDC +/- 10%

Power Consumption

- Transmit mode: 390mW
- Receive mode: 220mW
- Sleep mode: 15mW

Dimensions

110 (L) x 54 (W) x 5 (H) mm

Weight

41grams (adapter including antenna)

Operating Temperature

0° to 55 °C

Storage Temperature

-10° to 60 °C

Humidity

95% maximum (non-condensing)

EMI Certification

- FCC Class B
- CE Class B
- C-Tick
- DGT



Ordering Information

DWL-AG660

802.11a/g Wireless LAN CardBus Adapter

Please specify your order as follows:

DWL-AG660/AU	For Australia
DWL-AG660/SG	For Singapore
DWL-AG660/LA	For Latin America
DWL-AG660/FR	For France
DWL-AG660/EU	For Europe



Specifications subject to change without prior notice.
D-Link is a registered trademark of D-Link Corporation/D-Link System Inc. All other trademarks belong to their proprietors.

U.S.A	TEL: 1-800-326-1688	FAX: 1-866-743-4905
Canada	TEL: 1-905-8295033	FAX: 1-905-8295223
Europe (U. K.)	TEL: 44-20-8731-5555	FAX: 44-20-8731-5511
Germany	TEL: 49-6196-77990	FAX: 49-6196-7799300
France	TEL: 33-1-30238688	FAX: 33-1-30238689
Netherlands	TEL: 31-10-282-1445	FAX: 31-10-282-1331
Belgium	TEL: 32(0)2-517-7111	FAX: 32(0)2-517-6500
Italy	TEL: 39-02-2900-0676	FAX: 39-02-2900-1723
Sweden	TEL: 46-(0)8564-61900	FAX: 46-(0)8564-61901
Denmark	TEL: 45-43-969040	FAX: 45-43-424347
Norway	TEL: 47-99-300-100	FAX: 47-22-309580
Finland	TEL: 358-9-2707 5080	FAX: 358-9-2707-5081
Spain	TEL: 34-93-4090770	FAX: 34-93-4910795
Portugal	TEL: 351-21-8688493	
Czech Republic	TEL: 420-(603)-276-589	
Switzerland	TEL: 41-(0)-1-832-11-00	FAX: 41(0)-1-832-11-01
Greece	TEL: 30-210-9914 512	FAX: 30-210-9916902
Luxemburg	TEL: 32-(0)2-517-7111	FAX: 32(0)2-517-6500
Poland	TEL: 48-(0)-22-583-92-75	FAX: 48-(0)-22-583-92-76
Hungary	TEL: 36-(0)-1-461-30-00	FAX: 36-(0)-1-461-30-09
Singapore	TEL: 65-6774-6233	FAX: 65-6774-6322
Australia	TEL: 61-2-8899-1800	FAX: 61-2-8899-1868
India	TEL: 91-022-26526696	FAX: 91-022-26528914
Middle East (Dubai)	TEL: 971-4-3916480	FAX: 971-4-3908881
Turkey	TEL: 90-212-289-56-59	FAX: 90-212-289-76-06
Egypt	TEL: 202-414-4295	FAX: 202-415-6704
Israel	TEL: 972-9-9715700	FAX: 972-9-9715601
LatinAmerica	TEL: 56-2-232-3185	FAX: 56-2-232-0923
Brazil	TEL: 55-11-218-59300	FAX: 55-11-218-59322
South Africa	TEL: 27-12-665-2165	FAX: 27-12-665-2186
Russia	TEL: 7-095-744-0099	FAX: 7-095-744-0099 #350
China	TEL: 86-10-58635800	FAX: 86-10-58635799
Taiwan	TEL: 886-2-6600-0123	FAX: 886-2-6600-8168
Headquarters	TEL: 886-2-6600-0123	FAX: 886-2-6600-9898