



## Cat6 UTP Patch Cord

### INTRODUCTION

D-Link solid cables are the best twisted-pair cables in the market for transmitting data over local area Networks (LANs). These cables exceed performance requirements specified by the TIA/EIA-568B.2 / TIA/EIA-568C.2 and IEC 60603-7-4 standards.

As streaming video and multimedia over LAN are gaining popularity, users demand faster data transmission and reduced waiting time. D-Link cables are ideal for simple, cost-effective and high-speed transmission performance. They support a higher signal-to-noise ratio, providing better reliability for current applications and higher data rates for future applications.

### SPECIFICATIONS

- 4 Pairs Unshielded Twisted Pair (UTP) Cable
- Conductor Metal: Bare Copper
- Color Code: Gray
- Conductor: 24 AWG
- Insulation Material: HD-PE
- Jacket Material: PVC
- Heat-resistant: 60°C minimum (Temperature limited)

### MODULAR CONNECTOR/PLUG

- RJ-45 8P for Transparence color.
- Gold plated: 50U"
- Contact blade: Phosphor Bronze
- Temperature range: -10 ~ 80°C
- Dielectric withstanding voltage: 500V AC
- Insulation resistance: 35M Ohm (max.)
- Durability: 750 matching cycles
- Cable-to-plug tensile strength: 20lbs (89N) (min.)
- UL applications: 250V AC, 2A (max.)
- Polycarbonate (PC) UL94-V-0

### APPLICATION

- 10BASE-T, 100BASE-TX Fast Ethernet, 1000BASE-T (IEEE802.3)
- 100VG-AnyLAN (IEEE802.12)
- 550 MHz Broadband Video
- Voice, T1, ISDN
- 155/ 622 Mbps ATM
- Power over Ethernet (POE)

### APPROVAL / CERTIFICATION

- UL 444 (for Copper conductor)
- UL 758/ Style 2835
- UL 1581 (Test standard)
- Verified compliant with TIA/EIA-568C.2 standards by ETL, CUL listed, RoHs

Product No.	Description	Color
NCB-C6UYELR1-05	Cat6 UTP 24AWG Patch Cord, 0.5M	Yellow
NCB-C6UYELR1-1	Cat6 UTP 24AWG Patch Cord, 1M	Yellow
NCB-C6UYELR1-2	Cat6 UTP 24AWG Patch Cord, 2M	Yellow
NCB-C6UYELR1-3	Cat6 UTP 24AWG Patch Cord, 3M	Yellow
NCB-C6UYELR1-10	Cat6 UTP 24AWG Patch Cord, 10M	Yellow
NCB-C6UYELR1-15	Cat6 UTP 24AWG Patch Cord, 15M	Yellow