

CATEGORY 6 UTP KEYSTONES

NKJ-C6XXX1B21



NKJ-C6BLU1B21



NKJ-C6GRN1B21



NKJ-C6WHI1B21



NKJ-C6YEL1B21



NKJ-C61RED1B21

- RJ45 8P 8C 180C 50 Punch Down
- Jack Terminating 4 pairs, 22-26
- AWG Cable Universal labels color coded for T568A and T568B wiring schemes
- Fitting high density keystone panel UL, ETL, RoHS certified

SPECIFICATIONS

1. RJ45 Jack:
Housing: PC, UL94V-0 with Option Color
Contact Bracket: PC, UL94V-0 Transparent Colour
2. RJ45 Jack Contact:
Material: Phosphor Bronze with Nickel Plated
Finish: 50 micro-inch Gold plated on Plug Contact area
3. IDC:
Housing: PC, UL94V-0
Terminal: Phosphor Bronze with Tin plated
4. IDC CAP: PC, UL94V-0
5. PCB : FR4, UL 94V-0

PERFORMANCE

1. T568A & T568B wiring sticker
2. Insertion force: 20N max (IEC 60603-7-4) Retention
3. Strength : 7.7 kg between jack and plug Operation
4. Temperature : -10°C to 60C (ISO/IEC 11801, ANSI/TIA/EIA 568 C.2)
5. Life (Mating Cycles):
6. Jack: 750 cycle min (ISO/IEC 11801, IEC 60603-7-4)
7. IDC: suitable for 22-26 AWG stranded and solid wire, compatible with both 110 & Krone punch down tools
8. The Cat6 transmission performance is in compliance with the ANSI/TIA/EIA 568 C.2 standard

ORDERING INFORMATION

Product No.	Description	Color
NKJ-C6WHI1B21	Cat6 UTP Keystone Jack	White
NKJ-C6BLU1B21	Cat6 UTP Keystone Jack	Blue
NKJ-C6RED1B21	Cat6 UTP Keystone Jack	Red
NKJ-C6GRN1B21	Cat6 UTP Keystone Jack	Green
NKJ-C6YEL1B21	Cat6 UTP Keystone Jack	Yellow

ABS: Acrylonitrile Butadiene Styrene

