





Tablets  
Smart Phones

Universal  
Compatibility

1 USB-A  
2 USB-C

Fast Charge



The third-generation gallium nitride (GaN) semiconductor technology facilitates superior heat management within the charger, accelerating heat dissipation processes. Additionally, it delivers double the power density while concurrently mitigating power losses by 80%, resulting in a substantial enhancement in power efficiency.

### Product Highlights

- Cutting-Edge GaN Tech: Enjoy high-powered charging in a tiny package with the latest GaN 3.0 semiconductor material, making it ultra-portable.
- Convenient and Safe Design: Equipped with overcurrent, overvoltage, high temperature, and short circuit protection for stable and secure charging. It also features anti-interference and anti-static protection.
- Powerful Charging: With 100W support for Type C and 30W quick charge for USB A, it's perfect for charging laptops, tablets, smartphones, smartwatches, and even small fans.
- Universal Compatibility: Works seamlessly with a wide range of voltages, supporting 100V-240V/50-60Hz, ensuring it can be used anywhere.
- Versatile Quick Charging: Supports various quick charge protocols like Apple, QC, AFC, FCP, SCP, PD, PPS, PE, ensuring rapid charging for all your devices.

**Short Circuit Protection.** Safety feature in devices like chargers and power supplies. It prevents damage by cutting off current flow during a short circuit, ensuring safety and preventing hazards like overheating or fires

**Over Voltage Protection.** Safeguards electronic devices from damage due to high voltage levels. It monitors the voltage supply, activating measures to limit or cut off power if it exceeds safe levels. This prevents harm to sensitive components, like integrated circuits, ensuring device reliability and safety

**Over Current Protection.** Prevents damage from excessive current flow in electronic devices. It monitors current levels, activating safeguards if they exceed safe thresholds, ensuring device safety and reliability

### Specifications

Input:  
AC 100-240V, 50/60Hz, 1.5A Max  
Output:  
USB-A: 30W:5V/3A | 9V/3A  
Type-C:  
USB-C1 100W: (PPS 3.3-21V/5A) 5V/3A | 9V/3A | 12V/3A | 15V/3A | 20V/5A (100W Max)  
USB-C2 30W: 5V/3A | 9V/3A  
C1+C2: 65W+30W | C1+A: 65W+30W | C2+A: 30W | C1+C2+A:  
65W+30W